



FOAMULAR®

Extruded Polystyrene (XPS) Insulation

COMPETITIVE PRODUCTS COMPARISON SHEET

U.S. PRODUCTS ONLY

ASTM C578 Type	Minimum Compressive Strength (psi)	Owens Corning® FOAMULAR®	DOW STYROFOAM™	Kingspan®	Application
General Purpose					
X	15	FOAMULAR® 150 Square Edge (SE) Tongue and Groove (TG) Scored Square Edge (SSE)	UTILITYFIT™ Square Edge (SE) Tongue and Groove (TG) Scoreboard		Multi-purpose
IV	25	FOAMULAR® 250 Square Edge (SE) Tongue and Groove (TG) Scored Square Edge (SSE)	STYROFOAM™ Square Edge Tongue and Groove Scoreboard	GreenGuard® CM (Square Edge) SL (Ship Lap Edge) SB (Scoreboard)	Multi-purpose
IV	30	PINK-DRAIN®	PERIMATE™		Exterior foundation drainage and insulation
IV	25	INSUL-DRAIN®			Exterior foundation drainage and insulation with filter fabric
X	15	INSULPINK®	WALLMATE™		Slotted for furring strips on long edges for interior basement walls
X	15	INSULPINK® Z			For use beneath drywall in interior masonry wall applications. Fits between z-furring channels on 24" centers.
High Compressive Strength					
VI	40	FOAMULAR® 400	Highload 40	GreenGuard® Type VI 40 PSI Insulation Board	High load applications
VII	60	FOAMULAR® 600	Highload 60		High load applications
V	100	FOAMULAR® 1000	Highload 100		High load applications
Sheathing					
X	15	Half Inch	Residing Board	GreenGuard® Residing	Sheathing and residing
	15	Insulating Sheathing (IS)	Residential Sheathing (RS)	SLX Sheathing Board (25 psi)	Residential sheathing with plastic film facers on both sides
	15	PRO PINK® Insulating Sheathing	DURAMATE™ Plus		Insulating sheathing with extra-tough plastic film on both sides
Roofing					
X	18	THERMAPINK® 18	DECKMATE™ (16 psi)		Roofing new construction
IV	25	THERMAPINK® 25	DECKMATE™ Plus		Roofing new construction
VI	40	FOAMULAR® 404	ROOFMATE™		PRMA roofing
VI	40	FOAMULAR® 404 RB (Ribbed)	ROOFMATE™ – Ribbed		PRMA roofing, ribbed
VII	60	FOAMULAR® 604	PLAZAMATE™		Plaza deck and PRMA roofing
VII	60	FOAMULAR® 604 RB (Ribbed)			Plaza deck and PRMA roofing, ribbed
X		DURAPINK® ½" (18 psi)			Roofing recover board
Cavity Wall					
X	15	CW-15	CAVITYMATE™		Cavity wall insulation
IV	25	CW-25	CAVITYMATE™ Plus		Cavity wall insulation
IV	25	High R CW Plus	CAVITYMATE™ Ultra		Cavity wall insulation with R-5.6/inch
Low Temperature					
IV	30	LT 30 (Low Temperature)	FREEZERMATE™		Cold storage
IV	40	LT 40 (Low Temperature)	HI-40		Cold storage
Agricultural Products					
IV	25	AgTek	Ag Board		Agricultural: animal confinement buildings
FanFold Residing Products					
	10	FanFold	BLUECOR™	NPI4 (7 psi) (no facers) NP38 (9 psi) (no facers)	Residential residing
	10	DWB FanFold (10 psi)	Protection Board III (8 psi)	PB4 (16 psi)	Foundation dampproofing and waterproofing board
	10	PRO PINK® FanFold	HPU Layflat Insulation P/P	XPI4/PI450/XP38	Residential residing with plastic facers
	10	PRO PINK® FanFold Reflective	HPU Layflat Insulation P/R	XFPI4/FP38/FP1450/XFP38 (12 psi)	Residential residing with plastic and reflective facers

*Made to order (MTO), Minimum order, 1 truckload..



FOAMULAR®

Extruded Polystyrene (XPS) Insulation

COMPETITIVE PRODUCTS COMPARISON SHEET

U.S. PRODUCTS ONLY

ASTM C578 Type	Minimum Compressive Strength (psi)	Owens Corning® FOAMULAR®	DOW STYROFOAM™	Kingspan®	Application
Engineered Applications					
		COMPOSE XPS™			Graphic arts
		PINKCORE® TT	Panel Core		Lamination/tight tolerance
		Fabrication Billets	STYROFOAM™ PIB (ITW)		Pipe insulation
Ancillary Products					
		FoamSealR™	STYROFOAM™ Sill Seal	GreenGuard® Sill Sealer	Air Sealing
		JointSealR®	WEATHERMATE™ Straight Flashing	GreenGuard® Seam Tape	Foam joint air/water sealing
		FlashSealR®	WEATHERMATE™ Straight Flashing	GreenGuard® Butyl Flashing	Window and door flashing
		BILD-R-TAPE®	WEATHERMATE™ Construction Tape	GreenGuard® Seam Tape	Housewrap tape
		PINKWRAP®	WEATHERMATE™	GreenGuard® Classic Wrap	Housewrap
		TruWrap®	WEATHERMATE™ Plus	GreenGuard® Value Wrap	Housewrap
		raft-R-mate®			Attic ventilation

TRUCK LOADING DATA FOR FOAMULAR® XPS PRODUCTS

Product Dimensions	Square Feet per Pallet	Board Feet per Pallet	Bundles per Pallet	Pieces per Bundle	Pieces Per Pallet
¾ x 24 x 96	4,096	3,072	8	32	256
¾ x 24 x 96 (Half unit)	2,048	1,536	4	32	128
¾ x 48 x 96 (Half unit)	2,048	1,536	4	16	64
¾ x 48 x 96	4,096	3,072	8	16	128
¾ x 48 x 108	4,608	3,456	8	16	128
¾ x 48 x 120	5,120	3,840	8	16	128
1 x 24 x 96	3,072	3,072	8	24	192
1 x 24 x 96 (Half unit)	1,536	1,536	4	24	96
1 x 48 x 96 (Half unit)	1,536	1,536	4	12	48
1 x 48 x 96	3,072	3,072	8	12	96
1 x 48 x 108	3,456	3,456	8	12	96
1½ x 24 x 96	2,048	3,072	8	16	128
1½ x 48 x 96	2,048	3,072	8	8	64
2 x 24 x 96	1,536	3,072	8	12	96
2 x 24 x 96 (Half unit)	768	1,536	4	12	48
2 x 24 x 108	1,728	3,456	8	12	96
2 x 42 x 96	1,344	2,688	4	12	48
2 x 48 x 96	1,536	3,072	8	6	48
2½ x 24 x 96	1,152	2,880	8	9	72
2½ x 48 x 96	1,152	2,880	4	9	36
3 x 24 x 96	1,024	3,072	8	8	64
3 x 48 x 96	1,024	3,072	8	4	32
4 x 24 x 96	768	3,072	8	6	48
4 x 48 x 96	768	3,072	8	3	24

Truckload Conversions

Products that are 96" length: 12 pallets per truckload

Products that are 108" length: 10 pallets per truckload

Products that are 120" length: 8 pallets per truckload



FOAMULAR[®]

Extruded Polystyrene (XPS) Insulation

R-VALUES FOR FOAMULAR[®] XPS PRODUCTS

Thickness	Thermal Resistance, R-Value (180 day) minimum hr•ft ² •°F/Btu		Long Term Thermal Resistance, LTTR-Value, minimum hr•ft ² •°F/Btu
	@ 75° F	@ 40° F	@ 75° F
	FOAMULAR [®] XPS Products		
½"	3.0	3.2	N/A
¾"	4.0	4.3	N/A
1"	5.0	5.4	5.0
1½"	7.5	8.1	7.8
2"	10.0	10.8	10.6
2½"	12.5	13.5	13.4
3"	15.0	16.2	16.2
4"	20.0	21.6	22.0
High R CW Plus			
1¾"	10.0	10.8	10.3
2⅞"	12.0	13.0	12.5
3"	17.0	18.4	14.7

*R-value for FOAMULAR[®] IS and PROPINK[®] sheathing.

Note: R means the resistance to heat flow; the higher the value, the greater the insulation power. The insulation must be installed properly to get the marked R-value. Follow the manufacturer's instructions carefully. If a manufacturer's fact sheet is not provided with the material shipment, request this and review it carefully. R-values vary depending on many factors including the mean temperature at which the

test is conducted, and the age of the sample at the time of testing. Because rigid foam plastic insulation products are not all aged in accordance with the same standards, it is useful to publish comparison R-value data. The R-values for FOAMULAR[®] XPS insulation are provided from testing at two mean temperatures, 40°F and 75°F, and from two aging (conditioning) techniques, 180 day real time aged (as

mandated by ASTM C578) and a method of accelerated aging sometimes called "Long Term Thermal Resistance" (LTTR) per CAN/ULC S770. The R-value at 180 day real-time age and 75°F mean temperature is commonly used to compare products and is the value printed on the product.

Product comparisons based off data found in www.building.dow.com and www.greenguard.pactiv.com, May 2014.

Pub. No. 10017466-D. Printed in U.S.A. June 2016. THE PINK PANTHER™ & © 1964-2016 Metro-Goldwyn-Mayer Studios Inc. All Rights Reserved. The color PINK is a registered trademark of Owens Corning. © 2016 Owens Corning. All Rights Reserved.

